HALLIBURTON

SAFETY DATA SHEET

Product Trade Name: BORE-GEL®

Revision Date: 29-May-2018 Revision Number: 21

1. Identification

1.1. Product Identifier

Product Trade Name: BORE-GEL®

Synonyms None
Chemical Family: Mineral
Internal ID Code HM003576

1.2 Recommended use and restrictions on use

Application: Viscosifier

Uses advised against No information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier

Baroid Fluid Services

Product Service Line of Halliburton Energy Services, Inc.

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Halliburton Energy Services, Inc. 645 - 7th Ave SW Suite 1800

Calgary, AB T2P 4G8 Canada

Prepared By Chemical Stewardship

Telephone: 1-281-871-6107

e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number:

Emergency Telephone Number 1-866-519-4752 or 1-760-476-3962

Global Incident Response Access Code: 334305

Contract Number: 14012

2. Hazards Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

Carcinogenicity	Category 1A - H350
Specific Target Organ Toxicity - (Repeated Exposure)	Category 2 - H373

2.2. Label Elements

Hazard Pictograms



Signal Word: Danger

Hazard Statements H350 - May cause cancer by inhalation

H373 - May cause damage to organs through prolonged or repeated exposure if

inhaled

Precautionary Statements

Response

Prevention P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P314 - Get medical attention/advice if you feel unwell

Storage P405 - Store locked up

Disposal P501 - Dispose of contents/container in accordance with

local/regional/national/international regulations

2.3 Hazards not otherwise classified

This product contains Wyoming bentonite or other sorptive clays. Crystalline silica forms found in this particular clay are limited to quartz. Extreme temperatures that can generate cristobalite or tridymite are not expected to occur under realistic conditions. In addition, all quartz found in sorptive clays are considered "occluded", i.e., strongly coated with an amorphous silica surface. Occluded quartz has been experimentally-determined to be relatively non-toxic compared to unoccluded quartz. A lack of health effects found in several studies examining occupational exposure to sorptive clays also suggest that chronic inhalation of sorptive clays is not expected to result in silicosis or cancer. In light of these findings OSHA has recently exempted Wyoming bentonite and other sorptive clays from the crystalline silica PEL in §1910.1053(a)(1)(iii).

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Crystalline silica, quartz	14808-60-7	1 - 5%	Carc. 1A (H350)
			STOT RE 1 (H372)

The exact percentage (concentration) of the composition has been withheld as proprietary.

4. First Aid Measures

4.1. Description of first aid measures

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory

irritation develops or if breathing becomes difficult.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15

minutes and get medical attention if irritation persists.

Skin Wash with soap and water. Get medical attention if irritation persists.

Ingestion Under normal conditions, first aid procedures are not required.

4.2 Most important symptoms/effects, acute and delayed

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

All standard fire fighting media

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture

Special exposure hazards in a fire

None anticipated

5.3 Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters

Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use appropriate protective equipment. Avoid creating and breathing dust. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing.

See Section 8 for additional information

6.2. Environmental precautions

Prevent from entering sewers, waterways, or low areas.

6.3. Methods and material for containment and cleaning up

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. Handling and storage

7.1. Precautions for safe handling

Handling Precautions

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Information

Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Do not reuse empty container. Product has a shelf life of 36 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Crystalline silica, quartz	14808-60-7	TWA: 50 μg/m ³	TWA: 0.025 mg/m ³

Exposures to crystalline silica that result from bentonite or other sorptive clays are exempt from the PEL in $\S1910.1053$. The PEL in $\S1910.1000$ Table Z=3 (i.e., the formula that is approximately equivalent to $100 \mu g/m^3$) applies to occupational exposures to respirable crystalline silica from sorptive clays.

8.2 Appropriate engineering controls

Engineering ControlsUse approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Personal Protective Equipment If engineering controls and work practices cannot prevent excessive exposures,

the selection and proper use of personal protective equipment should be

determined by an industrial hygienist or other qualified professional based on the

specific application of this product.

Respiratory Protection If engineering controls and work practices cannot keep exposure below

occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or

other qualified professional.

Dust/mist respirator. (N95, P2/P3)

Hand Protection

on Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State: Powder Color Light brown or Gray
Odor: Mild earthy Odor No information available

Threshold:

Property Values

Remarks/ - Method

pH: 8-10

Freezing Point / Range No data available **Melting Point / Range** No data available **Boiling Point / Range** No data available **Flash Point** No data available Flammability (solid, gas) No data available Upper flammability limit No data available Lower flammability limit No data available **Evaporation rate** No data available **Vapor Pressure** No data available **Vapor Density** No data available

Specific Gravity 2.5

Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity

Partly soluble
No data available
No data available
No data available
No data available

Explosive Properties No information available

Oxidizing Properties No information available

9.2. Other information

VOC Content (%) No data available

10. Stability and Reactivity

10.1. Reactivity

Not expected to be reactive.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

Will Not Occur

10.4. Conditions to avoid

None anticipated

10.5. Incompatible materials

Hydrofluoric acid.

10.6. Hazardous decomposition products

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

11. Toxicological Information

11.1 Information on likely routes of exposure

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Acute Toxicity Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity"

subsection below).

Eye Contact May cause mechanical irritation to eye.

None known. **Skin Contact** None known. Ingestion

Chronic Effects/Carcinogenicity Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

> Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to

> humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2). There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

> This product contains Wyoming bentonite or other sorptive clays. Crystalline silica forms found in this particular clay are limited to quartz. Extreme temperatures that can generate cristobalite or tridymite are not expected to occur under realistic conditions. In addition, all quartz found in sorptive clays are considered "occluded", i.e., strongly coated with an amorphous silica surface (Wendlandt et al., 2007; Hochella and Muryama, 2010; SMI, 2014). Occluded quartz has been experimentally-determined to be relatively non-toxic compared to unoccluded quartz (Geh et al., 2006; Creutzenberg et al., 2008). A lack of health effects found in several studies examining occupational exposure to sorptive clays also suggest that chronic inhalation of sorptive clays is not expected to result in silicosis or cancer (Waxweiler et al., 1988; ACGIH, 1991; USEPA, 1996; IARC, 2005). In light of these findings OSHA has recently exempted Wyoming bentonite and other sorptive clays from the crystalline silica PEL in §1910.1053(a)(1)(iii).

11.3 Toxicity data

Toxicology	data	for	the	com	pone	nts
0 1 1				AC N.		

TOXICOlogy data for the			I DEO Danisal	L OFO Indicated
Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Crystalline silica, quartz	14808-60-7	> 15000 mg/kg (human)	No data available	No data available
	la.a	I		
Substances		Skin corrosion/irritation		
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin		
Substances	CAS Number	Serious eye damage/irritation		
Crystalline silica, quartz	14808-60-7	Non-irritating to the eye		
Substances	CAS Number	Skin Sensitization		
	14808-60-7	No information available.		
Crystalline silica, quartz	14606-60-7	ino information available.		
Substances	CAS Number	Respiratory Sensitization		
Crystalline silica, quartz	14808-60-7	No information available		
Substances	CAS Number	Mutagenic Effects		
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.		
Crystalline silica, quartz	14606-60-7	inot regarded as mutagemic.		
Substances	CAS Number	Carcinogenic Effects		
Crystalline silica, quartz	14808-60-7	Contains crystalline silica which ma	y cause silicosis, a delayed and pr	ogressive lung disease. The
		IARC and NTP have determined the	ere is sufficient evidence in human:	s of the carcinogenicity of
		crystalline silica with repeated resp	iratory exposure.	
Substances	CAS Number	Reproductive toxicity		
Crystalline silica, quartz	14808-60-7	No information available		
Substances	CAS Number	STOT - single exposure		
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in a	nimal studies at concentration requ	uiring classification.
Substances	CAS Number	STOT - repeated exposure		
Cancianoco	SAO HUMBEI	OTOT Tepeated exposure		

Crystalline silica, quartz	14808-60-7	Causes damage to organs through prolonged or repeated exposure if inhaled: (Lungs)	
Substances	CAS Number	Aspiration hazard	

12. Ecological Information

12.1. Toxicity

Substance Ecotoxicity Data

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Crystalline silica, quartz	14808-60-7	EC50 (72 h) =440 mg/L (Selenastrum capricornutum)(similar substance)	LL0 (96 h) =10000 mg/L (Danio rerio)(similar substance)	No information available	LL50 (24 h) >10000 mg/L (Daphnia magna)(similar substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Crystalline silica, quartz	14808-60-7	The methods for determining biodegradability are not
		applicable to inorganic substances.

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	CAS Number	Mobility
Crystalline silica, quartz	14808-60-7	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal methods If practical, recover and reclaim, recycle, or reuse by the guidelines of an

approved local reuse program. Should contaminated product become a waste, dispose of in a licensed industrial landfill according to federal, state, and local

regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. Transport Information

US DOT

UN Number Not restricted
UN proper shipping name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable
Environmental Hazards: Not applicable

Canadian TDG

UN Number Not restricted UN proper shipping name: Not restricted

Transport Hazard Class(es): Not applicable Packing Group: Not applicable Environmental Hazards: Not applicable

IMDG/IMO

UN Number
UN proper shipping name:
Transport Hazard Class(es):
Packing Group:
Environmental Hazards:
Not restricted
Not restricted
Not applicable
Not applicable

IATA/ICAO

UN Number Not restricted
UN proper shipping name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable
Environmental Hazards: Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Special Precautions for User None

15. Regulatory Information

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

TSCA Significant New Use Rules - S5A2

Substances	CAS Number	TSCA Significant New Use Rules - S5A2
Crystalline silica, quartz	14808-60-7	Not applicable

EPA SARA Title III Extremely Hazardous Substances

Substances	CAS Number	EPA SARA Title III Extremely Hazardous Substances
Crystalline silica, quartz	14808-60-7	Not applicable

EPA SARA (311,312) Hazard Class

Chronic Health Hazard

EPA SARA (313) Chemicals

Substances		Toxic Release Inventory (TRI) - Group I	Toxic Release Inventory (TRI) - Group II
Crystalline silica, quartz	14808-60-7	Not applicable	Not applicable

EPA CERCLA/Superfund Reportable Spill Quantity

21 / CERCE/ Caperiana Rope	t oznoznogonana koponasio opin quantity		
Substances	CAS Number	CERCLA RQ	
Crystalline silica, quartz	14808-60-7	Not applicable	

EPA RCRA Hazardous Waste Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65

Substances	CAS Number	California Proposition 65
Crystalline silica, quartz	14808-60-7	carcinogen

U.S. State Right-to-Know Regulations

Substances	CAS Number	MA Right-to-Know Law	NJ Right-to-Know Law	PA Right-to-Know Law
Crystalline silica, quartz	14808-60-7	Carcinogen	Present	Present

Extraordinarily hazardous

NFPA Ratings: Health 0, Flammability 0, Reactivity 0

HMIS Ratings: Health 0*, Flammability 0, Physical Hazard 0, PPE: At

Canadian Regulations

Canadian Domestic Substances All components listed on inventory or are exempt. List (DSL)

16. Other information

Preparation Information

Prepared By Chemical Stewardship

Telephone: 1-281-871-6107

e-mail: fdunexchem@halliburton.com

Revision Date: 29-May-2018

Reason for Revision SDS sections updated:

7

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms used in the safety data sheet

bw - body weight

CAS - Chemical Abstracts Service

d - day

EC50 – Effective Concentration 50%

ErC50 – Effective Concentration growth rate 50%

h - hour

LC50 - Lethal Concentration 50%

LD50 - Lethal Dose 50%

LL50 - Lethal Loading 50%

mg/kg - milligram/kilogram

mg/L - milligram/liter

mg/m³ - milligram/cubic meter

mm - millimeter

mmHg - millimeter mercury

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OEL - Occupational Exposure Limit

PEL – Permissible Exposure Limit

ppm – parts per million

STEL - Short Term Exposure Limit

TWA - Time-Weighted Average

UN - United Nations

w/w - weight/weight

Key literature references and sources for data

www.ChemADVISOR.com/

NZ CCID

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet