


# SAFETY DATA SHEET

Issuing Date 29-Oct-2014	Revision Date 16-Mar-2017	Revision Number 2
1. IDENTIFICATION OF TH	IE SUBSTANCE/PREPARATION AND	O THE COMPANY/UNDERTAKING
GHS product identifier		
Product Name	KOPR KOTE®	
Other means of identification		
Product Code(s)	105	
Synonyms	MIL PRF-907F,	
Recommended use of the chemica	l and restrictions on use	
Recommended Use	Lubricants, Greases and Release Products	
Uses advised against	No information available	
Supplier's details		
Manufacturer Address Jet-Lube, LLC 930 Whitmore Dr. Rockwall, Texas 75087 TEL: 972-771-1000 Toll Free: 1-800-669-6318		
Emergency telephone number		
Emergency Telephone Number	CHEMTREC: +1-703-527-3887 (INTERNAT 1-800-424-9300 (NORTH AMERICA)	IONAL)
Classification	2. HAZARDS IDENTIFICATIO	N
Classification		
This chemical is considered hazardo	us according to the OSHA Hazard Communicat	ion Standard 2012 (29 CFR 1910.1200)
Skin Corrosion/Irritation		Category 2
Serious Eye Damage/Eye Irritation		Category 2
GHS Label elements, including pre	cautionary statements	

# **Emergency Overview**

Signal Word Hazard Statements Warning

Causes skin irritationCauses serious eye irritation



## **Precautionary Statements**

Prevention

- Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

#### **General Advice**

· Specific treatment is urgent (see supplemental first aid instructions on this label)

#### Eyes

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• If eye irritation persists: Get medical advice/attention.

#### Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

## Storage

None

#### Disposal

None

## Hazard Not Otherwise Classified (HNOC)

Not applicable

#### Other information

20% of the mixture consists of ingredient(s) of unknown toxicity.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	74869-21-9	50-70	*
Graphite	7782-42-5	10-15	*
Copper	7440-50-8	8-13	*
Talc	14807-96-6	1-5	*
Limestone	1317-65-3	1-5	*
Molybdenum (IV) sulfide	1317-33-5	1-5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# **4. FIRST AID MEASURES**

# Description of necessary first-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Drink plenty of water. Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. If symptoms persist, call a physician.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician

Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Water spray. Carbon dioxide (CO<sub>2</sub>). Foam. Dry powder. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

# Specific Hazards Arising from the Chemical

Burning produces obnoxious and toxic fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Heavy metal compounds

Explosion Data
Sensitivity to Mechanical Impact
Sensitivity to Static Discharge

None. None.

# Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective e	guipment and emergency procedures
Personal Precautions	Use personal protective equipment.
Environmental Precautions	
Environmental Precautions	Do not allow material to contaminate ground water system. Prevent product from entering drains. See Section 12 for additional Ecological Information.
Methods and materials for contain	ment and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling

Wear personal protective equipment. Ensure adequate ventilation.

# Conditions for safe storage, including any incompatibilities

Storage

Keep container tightly closed in a dry and well-ventilated place. Keep in a bunded area

Incompatible Products

Strong oxidizing agents. Acetylene. Vinyl compounds.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Control parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	-	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	IDLH: 1000 mg/m <sup>3</sup> containg no asbestos and <1% quartz TWA: 2 mg/m <sup>3</sup>
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m <sup>3</sup> Mo inhalable fraction TWA: 3 mg/m <sup>3</sup> Mo respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> Mo	IDLH: 5000 mg/m³ Mo

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

Engineering MeasuresShowers<br/>Eyewash stations<br/>Ventilation systemsIndividual protection measures, such as personal protective equipmentEye/Face Protection<br/>Skin and Body Protection<br/>Respiratory ProtectionSafety glasses with side-shields. Risk of contact, wear: Goggles.<br/>Impervious clothing. Impervious gloves.<br/>None required under normal usage. If exposure limits are exceeded or irritation is<br/>experienced, NIOSH/MSHA approved respiratory protection should be worn.Hygiene MeasuresWhen using, do not eat, drink or smoke. Remove and wash contaminated clothing before<br/>re-use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Semi-fluid (gel)	Appearance	Copper Bronze
Odor	Petroleum like	Odor Threshold	No information available
<u>Property</u>	Values	<u>Remarks/ - Me</u>	thod
рН	Neutral	None known	
Melting Point/Range	> 232 °C	None known	
Boiling Point/Boiling Range	< 316 °C	None known	
Flash Point	> 221 °C	None known	
Evaporation rate	<0.01	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		
Vapor Pressure	<0.01 kPa @ 20°C	None known	
Vapor Density	>5 (air = 1)	None known	
Specific Gravity	1.15	None known	
Water Solubility	Insoluble in water.	None known	
Solubility in other solvents	Largely.	None known	
Partition coefficient: n-octane	ol/waterNo data available	None known	
Autoignition Temperature	> 260 °C / >500 °F	None known	
<b>Decomposition Temperature</b>	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties	Not flammable		
Explosive Properties	No data available		
Oxidizing Properties	No data available		
0			
Other information			
VOC Content (%)	None		
VOC (g/l)	None		
100 (9.1)			

# **10. STABILITY AND REACTIVITY**

## **Reactivity**

No data available.

# **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Incompatible products.

#### **Incompatible materials**

Strong oxidizing agents. Acetylene. Vinyl compounds.

#### Hazardous decomposition products

None known based on information supplied.

# **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Product Information	
Inhalation	None known.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Ingestion	Not an expected route of exposure. May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating greases A complex combination of	= 2280 mg/kg (Rat)	-	-
hydrocarbons having carbon			
numbers predominantly in the range			
of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.			

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Contains no ingredients above reportable quantities listed as a carcinogen.
Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

## Numerical measures of toxicity - Product

Acute Toxicity20% of the mixture consists of ingredient(s) of unknown toxicity.The following values are calculated based on chapter 3.1 of the GHS document:LD50 Oral2606 mg/kg; Acute toxicity estimate

# **12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

Aquatic toxicity is unlikely due to low solubility. Based on available data, the classification criteria are not met

Lc50/48h/Acartia tonsa = >1000 mg/L EC50/72h/Skeletonema costatum = >1000 mg/L LC50/96h/Scophthalmus maximus = >1000 mg/L

Sea sediment LC50/10d/Corophium sp. = 925-3502 mg/kg

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc. 74869-21-9	>1001 mg/l	LC50 96 h: > 2000 mg/L (Salmo gairdneri)		

#### WPS-JLI-001US -KOPR KOTE®

Copper	EC50 96 h: 0.031 - 0.054	LC50 96 h: 0.0068 - 0.0156	-	EC50 48 h: = 0.03 mg/L
7440-50-8	mg/L static	mg/L (Pimephales		Static (Daphnia magna)
	(Pseudokirchneriella	promelas)		
	subcapitata)	LC50 96 h: < 0.3 mg/L static		
	EC50 72 h: 0.0426 - 0.0535	(Pimephales promelas) LC50		
	mg/L static	96 h: = 0.052 mg/L		
	(Pseudokirchneriella	flow-through (Oncorhynchus		
	subcapitata)	mykiss)		
		LC50 96 h: = 0.112 mg/L		
		flow-through (Poecilia		
		reticulata)		
		LC50 96 h: = 0.2 mg/L		
		flow-through (Pimephales		
		promelas)		
		LC50 96 h: = 0.3 mg/L semi-		
		static (Cyprinus carpio) LC50		
		96 h: = 0.8 mg/L static		
		(Cyprinus carpio)		
		LC50 96 h: = 1.25 mg/L		
		static (Lepomis macrochirus)		
Talc		LC50 96 h: > 100 g/L		
14807-96-6		semi-static (Brachydanio		
		rerio)		

Persistence and Degradability

No information available.

**Bioaccumulation** 

No information available.

# **Other Adverse Effects**

No information available.

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with federal, state, and local regulations Where possible recycling is preferred to disposal or incineration.

# **Contaminated Packaging**

Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Copper	Toxic	

# **14. TRANSPORT INFORMATION**

DOT	Not regulated
TDG_	Not regulated
<u>MEX</u>	Not regulated
ICAO	Not regulated
IATA	Not regulated
IMDG/IMO	Not regulated
RID	Not regulated
ADN	Not regulated
ADR_	Not regulated

# **15. REGULATORY INFORMATION**

## International Inventories

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Copper	7440-50-8	8-13	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	Х	
		•	•	

#### <u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

# U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

## U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Graphite	Х	Х	Х		Х
Copper	Х	Х	Х	Х	Х
Talc	Х	Х	Х		Х
Limestone	Х	Х	Х		Х

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION				
<u>NFPA</u>	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 1	Physical Hazard 0	Personal Protection X
Prepared By	23 Britis	Stewardship h American Blvd.		

	20 Diffior American Diva.
	Latham, NY 12110
	1-800-572-6501
Issuing Date	29-Oct-2014
Revision Date	16-Mar-2017
Revision Note	Updated company information.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet